

ANTIGELO PRONTO -22

Ready to use antifreeze

DESCRIPTION

Ethylene glycol-based permanent antifreeze fluid; added with a special amine and nitrite free of inhibitors.

AREAS OF APPLICATION

Suitable for any type of sealed circuit, it prevents foaming and encrustation without attacking rubber or plastic components (sleeves, gaskets). Protects metal parts of the circuit from corrosion (Aluminium, Copper, Brass, Cast iron, Steel, etc.).

FEATURES

- Ready to use
- Anti-corrosive and anti-foaming action
- Inhibits scale formation
- Available in 1 litre and 5 litres

TECHNICAL DATA

Appearance	Liquid
Colour	Blue
Specific Gravity [kg/dm ³] (relative alla base)	Ca. 1.06
pH (ASTM D1287)	> 8.5
Boiling point [°C] (ASTM D1120)	Ca. 105
Freezing point [°C]	-22
Water Solubility	complete

APPLICATION

Ready to use product, do not dilute further with water. It is compatible with any other liquid antifreeze liquid.

CLEANING OF EQUIPMENT AND PERSONAL PROTECTIVE MEASURES

Take care when handling and using the product, use protective disposable gloves if necessary. In case of skin contact, simply wash with soap and water.

PACKAGING

Bottle 1000 ml	24 pieces per box
Bottle 5000 ml	4 pieces per box

STORAGE AND SHELF LIFE

The product can be stored for 24 months in its original packaging. Storage temperature between 5°C to 30°C in a cool, dry place. Keep away from sources of humidity, heat and direct contact with direct sunlight.

GENERAL INFORMATION

The information contained in this data sheet represents the best of our knowledge. However, this document cannot be regarded as a guarantee that the product will be used and applied in accordance with the instructions provided. Successful application is beyond our control and depends on many factors. We accept no responsibility for the misuse of the product, the recommendations in this document should be considered general guidelines. If any doubts remain, please carry out preliminary tests. NPT Srl, reserves the right to modify and update the data sheet without prior notice. Customers are kindly requested to check that they have the latest version.

ALWAYS CONSULT THE SAFETY DATA SHEET BEFORE USING THE PRODUCT